

Qty.	Description
------	-------------

1	CR 10-5 A-A-A-E-HQQE
---	----------------------



Note! Product picture may differ from actual product

Product No.: [96500983](#)

Vertical, non-self-priming, multistage, in-line, centrifugal pump for installation in pipe systems and mounting on a foundation.

The pump has the following characteristics:

- Impellers and intermediate chambers are made of Stainless steel, EN 1.4301.
- Pump head and base are made of Cast iron.
- The shaft seal has assembly length according to EN 12756.
- Power transmission is via cast iron split coupling.
- Pipework connection is via Oval / Rp flanges.

The motor is a 3-phase AC motor.

Controls:

Terminal box position: 6

Frequency converter: None

Liquid:

Pumped liquid: Water

Liquid temperature range: -20 .. 120 °C

Selected liquid temperature: 20 °C

Density: 998.2 kg/m³

Technical:

Pump speed on which pump data are based: 2899 rpm

Rated flow: 10 m³/h

Rated head: 40.7 m

Pump orientation: Vertical

Shaft seal arrangement: Single

Primary shaft seal: HQQE

Code for shaft seal: HQQE

Approvals: CE,EAC,UKCA,SEPRO,RCM,

Approvals for drinking water: WRAS,ACS

Curve tolerance: ISO9906:2012 3B

Materials:

Qty.	Description
1	Type key, code for rubber components. E = EPDM, V=FKM: E Base: Cast iron EN 1561 EN-GJL-250 ASTM A48-35B Impeller: Stainless steel EN 1.4301 AISI 304 Type key, code for materials: A Bearing: SIC Installation: Maximum ambient temperature: 60 °C Maximum operating pressure: 16 bar Max pressure at stated temp: 16 bar / 120 °C 16 bar / -20 °C Type of connection: Oval / Rp Size of inlet connection: 1 1/2 inch Size of outlet connection: 1 1/2 inch Pressure rating for connection: PN 16 Flange size for motor: FT115 Terminal box position: 6 Electrical data: Motor standard: IEC Motor type: 90LE Rated power - P2: 2.2 kW Power (P2) required by pump: 2.2 kW Mains frequency: 50 Hz Rated voltage: 3 x 220-240D/380-415Y V Rated current: 8.00/4.60 A Starting current: 840-920 % Cos phi - power factor: 0.86-0.80 Rated speed: 2890-2910 rpm IE Efficiency class: IE3 Motor efficiency at full load: 85.9 % Motor efficiency at 3/4 load: 88.2-87.2 % Motor efficiency at 1/2 load: 88.0-85.5 % Number of poles: 2 Enclosure class (IEC 34-5): IP55 Dust/Jetting Insulation class (IEC 85): F Built-in motor protection: NONE Motor No: 85U01908 Others: Minimum efficiency index, MEI ≥: 0.70 Net weight: 49 kg Gross weight: 53 kg



Company name:

Created by:

Phone:


Date:

9/9/2026


Qty.	Description
------	-------------

1	Shipping volume: 0.104 m ³
	Danish VVS No.: 385903050
	Swedish RSK No.: 5856246
	Norwegian NRF no.: 9040461


96500983 CR 10-5 A-A-A-E-HQQE 50 Hz






Pumped liquid = Water
 Liquid temperature during operation = 20 °C
 Density = 998.2 kg/m³



Description	Value
General information:	
Product name:	CR 10-5 A-A-A-E-HQQE
Product No:	96500983
EAN number:	5700396213019
Price:	
Technical:	
Pump speed on which pump data are based:	2899 rpm
Rated flow:	10 m³/h
Rated head:	40.7 m
Maximum head:	51.1 m
Stages:	5
Impellers:	5
Number of reduced-diameter impellers:	0
Low NPSH:	N
Pump orientation:	Vertical
Shaft seal arrangement:	Single
Primary shaft seal:	HQQE
Code for shaft seal:	HQQE
Approvals:	CE, EAC, UKCA, SEPRO, RCM,
Approvals for drinking water:	WRAS, ACS
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Model:	A
Pump type:	CR
Materials:	
Type key, code for rubber components. E = EPDM, V=FKM:	E
Base:	Cast iron
	EN 1561 EN-GJL-250
	ASTM A48-35B
Impeller:	Stainless steel
	EN 1.4301
	AISI 304
Type key, code for materials:	A
Code for rubber:	E
Bearing:	SIC
Installation:	
Maximum ambient temperature:	60 °C
Maximum operating pressure:	16 bar
Max pressure at stated temp:	16 bar / 120 °C
	16 bar / -20 °C
Type key, code for pipework connection:	A
Type of connection:	Oval / Rp
Size of inlet connection:	1 1/2 inch
Size of outlet connection:	1 1/2 inch
Pressure rating for connection:	PN 16
Flange size for motor:	FT115
Terminal box position:	6
Connect code:	A
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-20 .. 120 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	



Pumped liquid = Water
Liquid temperature during operation = 20 °C
Density = 998.2 kg/m³





Company name:

Created by:


Phone:

Date:



9/9/2026

Description	Value
Motor standard:	IEC
Motor type:	90LE
Rated power - P2:	2.2 kW
Power (P2) required by pump:	2.2 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 220-240D/380-415Y V
Rated current:	8.00/4.60 A
Starting current:	840-920 %
Cos phi - power factor:	0.86-0.80
Rated speed:	2890-2910 rpm
IE Efficiency class:	IE3
Motor efficiency at full load:	85.9 %
Motor efficiency at 3/4 load:	88.2-87.2 %
Motor efficiency at 1/2 load:	88.0-85.5 %
Number of poles:	2
Enclosure class (IEC 34-5):	IP55 Dust/Jetting
Insulation class (IEC 85):	F
Built-in motor protection:	NONE
Motor No:	85U01908
Controls:	
Terminal box position:	6
Frequency converter:	None
Others:	
Minimum efficiency index, MEI ≥:	0.70
Net weight:	49 kg
Gross weight:	53 kg
Shipping volume:	0.104 m ³
Danish VVS No.:	385903050
Swedish RSK No.:	5856246
Norwegian NRF no.:	9040461

96500983 CR 10-5 A-A-A-E-HQQE 50 Hz



96500983 CR 10-5 A-A-A-E-HQQE 50 Hz



Note! All units are in [mm] unless others are stated.